

Price Management



Retail Branding and
Information Solutions

Avery Dennison® 9485 Portable Printer

Accelerate performance in price and item identification in the store, reducing complexity while improving speed, efficiency and accuracy.

IMPROVE IN-STORE EFFICIENCY THROUGH ENHANCED PRODUCTIVITY

Designed to improve in-store efficiency through enhanced productivity of retail price-marking applications. Compatible with virtually any data collection terminal on the market.

The Avery Dennison 9485 portable printer can increase your productivity when performing the following applications:

- Re-tagging, reticketing and markdowns
- Shelf-edge labeling and shelf-talker signage
- Sell-by and reduced-to-clear labeling
- Returns marking
- Promotional labeling
- Item marking

PALM-SIZED PRODUCTIVITY

Smaller and lighter than the competition, this compact portable printer is designed to be worn for everyday use without fatiguing your associates.

ACCELERATED PRICEMARKING

Innovative peel functionality enables efficient label printing and faster re-pricing, making the item available again immediately for sale.

IMPROVED CUSTOMER SERVICE

Markdowns are performed right on the sales floor instead of the associate walking to the back room for markdown labels. That means the associate stays on the floor, available to help customers.

ENHANCED POWER MANAGEMENT

Intelligent, configurable sleep mode saves the battery power for when you need it, maximizing productivity by printing more labels on a single charge.

RUGGED

Drop-tested from five feet (1.4m) to ensure the printer will continue operation working normally, even after being dropped.

HIGH LEVEL OF SECURITY COMPLIANCE FOR THE MOST SENSITIVE APPLICATIONS

Enterprise security connectivity brings wired security to WLAN networks by employing the latest data encryption and authentication standards. This ensures reliability and enables straight forward integration into your system.

ELEVATING BRANDS. ACCELERATING PERFORMANCE.

Experience this and many other supply chain solutions at our worldwide Customer Design and Innovation Centers. For more information on the Avery Dennison 9485 portable printer or to schedule a tour of our Customer Design and Innovation Centers, please call 800.543.6650, prompt 5, or e-mail rbis.solutions@averydennison.com.

For more information or complete warranty and other terms and conditions, please contact your Avery Dennison representative or visit our website at www.rbis.averydennison.com.



Intelligent, creative and sustainable solutions that elevate brands and accelerate performance throughout the global retail supply chain.

rbis.averydennison.com

Price Management

Avery Dennison® 9485 Portable Printer

STANDARD FEATURES

DIMENSIONS

Height: 5.9" (152mm)
Width: 3.97" (101mm)
Depth: 2.87" (73mm)

WEIGHT

1.30 lbs (0.59 kg)

SHIPPING WEIGHT

1.52 lbs (0.69 kg)

PRINTING METHOD

Thermal Direct

PRINTHEAD

1.89" (48mm); 203 DPI (8 dots/mm)

MEMORY

8MB RAM, 16MB Flash

ONE-DIMENSIONAL BAR CODES

UPCA +2/+5, UPCE +2/+5, EAN8 +2/+5, EAN13 +2/+5, EAN 128, Interleaved 2 of 5, Extended Code 39, Codabar (NW7), Code 128, Code 93, Postnet, GS1 Databar (RSS or Composite Code)

TWO-DIMENSIONAL BAR CODES

PDF417, MaxiCode, Aztec, QR Code (Quick Response), Datamatrix

STANDARD FONTS

7 resident bitmap fonts with point sizes of 12 to 48 points; 1 scalable font (Arial type font 5 to 90 point)

TRUETYPE™ FONTS

Downloadable TrueType fonts supported – thousands available

FONT ROTATION

Fonts rotated at 0, 90, 180, 270 degrees

SENSING METHOD

Black mark, die cut and non-indexed

DISPLAY

10 character mono-graphic LCD white backlit display, 128 x 64 dots
Display size: 1.3" x .7" (34mm x 17.5mm)

PRINTER CONTROL LANGUAGES

MPCL II or CPCL compatible

PRINTER WARRANTY

One (1) year parts and labor

PRINTHEAD WARRANTY

One (1) million inches (25,400M) or six (6) months, whichever occurs first.

BATTERY AND CABLE WARRANTY

Three (3) months pro-rated from date of shipment. Physical damage to the batteries or cables will not be covered by the limited warranty.

SUPPLIES

Only Avery Dennison supplies are recommended. Use non-perforated supplies in peel mode, butt cut, die cut or non-indexed.

SUPPLY TYPES

Labels, tags, paper

SUPPLY SIZES

Width in continuous or peel mode:
0.5" to 2.28" (12.7mm to 57.9mm);
Length Cont.: 0.7" to 11.8" (17.8mm to 299mm)
Peel: 0.5" to 11.8" (12.7mm to 299.3mm)

SUPPLY ROLL SIZES

2.2" (56mm) OD on a 1" (25.4mm) core

SUPPLY THICKNESS

0.0024" – 0.007" (0.06mm - 0.18mm)

MAXIMUM PRINT AREA

1.89" x 11.8" (48mm x 300mm)

ENVIRONMENTAL RANGES

OPERATING TEMPERATURE

14° to 122° F (-10° C to 50° C)

STORAGE

-4° to 140° F (-20° C to 60° C)

HUMIDITY/OPERATING AND STORAGE

10% to 90% non-condensing

ELECTROSTATIC DISCHARGE AND AIR QUALITY

Some problems with electronic equipment may occur in environments prone to static discharge or extreme dust conditions. Avery Dennison suggests that you take precautions to minimize these problems.

PERFORMANCE

POWER SOURCE

7.4v Lithium Ion Battery

PRINT RATIO

25% black maximum per square inch (mm)

INCHES PER CHARGE

Up to 6,000 inches of 25% black printing at 3.0 IPS (76.2mm/sec) on the supply. Inches per charge vary according to setup and usage.

BATTERY LIFE CYCLE

Approximately 300 full discharge cycles. Cycle life is approximate. Many factors affect an individual battery's performance.

RECOMMENDED DUTY CYCLE

Duty cycle (5 minutes out of 15 15-minutes time intervals). On-demand or intermittent printing has no restrictions.

PRINT SPEED

Up to 3 ips (76.2mm/sec)

COMMUNICATIONS

STANDARD COMMUNICATION PORTS

USB 2.0

RS 232 – mini din connector

OPTIONS AND ACCESSORIES

OPTIONS

Wireless Networking – 802.11 b/g;
WLAN: 802.11b/g; Encryption: WEP 64, WEP 128, WPA, WPA 2;
Authentication Types: Shared and Open system, TTLS, PEAP, PSK, EAP-FAST; Authentication Protocols: PAP, MSCHAP_V2; Remote printer management

Bluetooth V2.1

ACCESSORIES

Single station battery charger
Four Four-station battery charger
Extra battery
Belt Clip
Shoulder Strap

Specifications subject to change without notice.



Retail Branding and
Information Solutions

AMERICAS

1700 West Park Drive
Suite 400
Westborough
MA 01581
USA
Toll Free +1 800 444 4947
International +1 336 621 2570

ASIA

15/F, Octa Tower
8 Lam Chak Street
Kowloon Bay, Kowloon
Hong Kong
Tel +852 3146 8100
Fax +852 2785 1255
Fax +1 336 544 5040

EASTERN EUROPE, MIDDLE EAST AND AFRICA

TEM Otoyolu Atı Alanı Mevkii,
Tekstilkent Koza Plaza A Blok
Kat: 17-18 34235, Esenler
Istanbul
Turkey
Tel +90 212 467 4000
Fax +90 212 467 4001

WESTERN EUROPE

Kempische Kaai 7C
3500 Hasselt
Belgium
Tel +32 11 28 77 24
Fax +32 11 28 77 29

Elevating brands and
accelerating performance
throughout the global
retail supply chain

The information contained herein is believed to be reliable but Avery Dennison makes no representations concerning the accuracy or correctness of the data. This product, like any other should be tested by the customer/user thoroughly under end user conditions to ensure the product meets the particular requirements. Independent results may vary.

Avery Dennison and the logo are registered trademarks of Avery Dennison Corp.

Third party trademarks and/or trade names used herein are the property of their respective owner(s).

© 2015 Avery Dennison Corporation, All Rights Reserved.

1216SNG.ENG01.0115LT.RBIS

rbis.averydennison.com