

Inventory Accuracy, Visibility and Loss Prevention

Avery Dennison® 9906 Tabletop Bar Code Printer

Elevating Brands and Accelerating Performance Throughout the Global Retail Supply Chain



Accelerate Performance: Inventory Accuracy, Loss Prevention and Visibility

Improve Inventory Management, Loss Prevention and Visibility through integrated solutions along the Global Retail Supply Chain that increase speed, accuracy, visibility, productivity and margins.

Durable, Reliable and Easily Integrated

The Avery Dennison 9906 Printer has a large graphical display for a user-friendly menu system as well as support for Asian fonts. The right choice for retailers or distribution centers printing less than 10,000 labels or tags per week, including:

- Shipping labels
- Replacement tags
- Routing labels

Compact, Sleek and Quiet

The compact design of the 9906 ensures it fits into some of the tightest workspaces in distribution centers and retail stores.

Its design and low-noise printing output avoid disruption to the retail customer experience.

Elevates Brand

Prints identical replacement tags that are indistinguishable from the tags applied at the source. Customers won't be able to tell if the item has been retagged.

Decreases Downtime

The unique ribbon tensioning system means fewer parts to maintain and replace, reducing costs and avoiding downtime in your inventory control process.

Data Stream Flexibility

Full range of connectivity options, including RS-232, USB 2.0, Ethernet and wireless 802.11b/g networking. Material handling options including liner peel, liner take-up, and ticket and tag cutting.

Elevating Brands. Accelerating Performance.

To learn more or receive complete warranty information as well as other terms and conditions, please contact your Avery Dennison representative or visit our website at www.monarch.averydennison.com.



Inventory Accuracy, Visibility and Loss Prevention

Avery Dennison® 9906 Tabletop Bar Code Printer

Elevating Brands and Accelerating Performance Throughout the Global Retail Supply Chain



Avery Dennison® 9906 Tabletop Bar Code Printer

Standard Features

Dimensions

Height: 279 mm (11")
Width: 267 mm (10.5")
Depth: 409 mm (16.1")

Weight:

10 kg (22.1 lbs)

Shipping Weight:

11.4 kg (25 lbs)

Printing Method:

Thermal direct or Thermal transfer

Printhead:

Width: 102 mm/812 dots (4.09")
8 dots/mm/203 dpi
12 dots/mm/300 dpi

Memory:

Model BA:
4 MB Flash, 16 MB SDRAM
Model EF:
32 MB Flash, 32 MB SDRAM

Bar Codes:

UPCA +2/+5, UPCE +2/+5, EAN8 +2/+5, EAN13 +2/+5, EAN128 Interleaved 2 of 5, Extended Code 39, Codabar (NW7), Code 128, Code 16K, Code 93, MSI, Postnet, Intelligent Mail, GS1 Databar, PDF417, Maxi-Code, Data Matrix (ECC-200), Quick Response (QR Code), Aztec

Standard Fonts:

Bitmap - Standard, Reduced, Bold, OCRA-like, CG Triumvirate, and CG Triumvirate Bold
TrueType® - EFF Swiss Bold

Font Magnification:

1x to 7x for Bitmapped fonts, 4 to 250 pt. for scalable / TrueType™ fonts

Standard PC/Host Interface:

RS-232C Serial (115, 200 BPS)
USB 2.0 Host; USB 2.0 Device

Sensing Method:

Edge justified, die cut, black mark, aperture

Printer Control Language(s):

MPCL, Easyplug, MLI

Printer Warranty:

One (1) year parts and labour.
Full written warranty statement available upon request.

Printhead Warranty:

One (1) million inches or six (6) months, whichever occurs first

Supplies

Only Avery Dennison supplies are recommended.

Supply Types:

Labels and Tags

Supply Sizes:

Width: 19 mm to 114 mm (0.75" to 4.5")
Length: 13 mm to 1270 mm (0.50" to 50")
Width with peel: 38 mm to 108 mm (1.5" - 4.25")
Maximum length with indexed supplies: 445 mm (17.5")
Supply Roll OD: 8" on 3" core

Typical Supply Roll Length:

150 m (492')

Supply Thickness:

0.1397 mm to 0.2540 mm (0.0055" to 0.010")

Ribbon Length:

450 m (1476.38')

Environmental Ranges

Operating Temperature:

Thermal Transfer:
4° to 35°C (40° to 95°F)
Thermal Direct:
4° to 40°C (40° to 104°F)

Storage:

-10° to 49°C (15° to 120°F)

Humidity/Operating and Storage:

5% to 90% non-condensing

Electrostatic Discharge and Air Quality:

Some problems with electronic equipment may occur in environments prone to static discharge or extreme dust conditions. Avery Dennison suggests that you take precautions to minimize these problems.

Performance

Power Source:

90-264 VAC with
Auto select 50/60 Hz

Print Speed:

- 64 mm/s (2.5 ips) - default for serial bar codes
- 102 mm/s (4.0 ips)
- 152 mm/s (6.0 ips) - default for parallel bar codes

Option & Accessories

Options:

- Peel mode with on demand sensor
- Peel mode with liner take-up
- Tear bar with peel mode
- 300 dpi printhead
- ADK script programming for special applications
- Internal Ethernet with MonarchNet2™
- 802.11 b/g wireless with MonarchNet2™
- Parallel port (IEEE-1284)
- Tag cutter

Accessories:

- 935 Rewind
- 939i Keypad
- USB QWERTY keyboard
- 929 Tag catch tray

In our ongoing effort to deliver the best technology, specifications are subject to change without notice.

The information contained herein is believed to be reliable but Avery Dennison makes no representations concerning the accuracy or correctness of the data. This product, like any other, should be tested by the customer/user thoroughly under end user conditions to ensure the product meets the particular requirements. Independent results may vary. Avery Dennison and the logo are registered trademarks of Avery Dennison Corp. Third party trademarks and/or trade names used herein are the property of their respective owner(s). Avery Dennison liability is limited to the replacement value of defective products. In no event shall Avery Dennison be held liable for consequential, indirect or incidental damages. Products, information and specifications are subject to change without notice.

Avery Dennison and the logo are registered trademarks of Avery Dennison Corp. Third party trademarks and/or trade names used herein are the property of their respective owner(s).

© 2014 Avery Dennison Corporation, All Rights Reserved.

Avery Dennison Retail Branding and Information Solutions

Avery Dennison
Deutschland GmbH
Ohmstrasse 3
D-85386 Eching
Tel +49 (0) 8165 925 299
info.deutschland@eu.averydennison.com

Avery Dennison
BV Nederland
St. Laurensdreef 40
3565 AK Utrecht
Tel +31 (0) 30 263 22 33
hardware.benelux@eu.averydennison.com

Avery Dennison
France
10-12 Rue du Saule Trapu - BP 217
91882 Massy Cedex
Tel +33 (0) 1 69 53 56 00
communication.france@eu.averydennison.com

Avery Dennison
Scandinavia
Bergfotsgatan 3A
S-431 35 Mölndal
Tel +46 31 68 30 40
info.se@eu.averydennison.com

Avery Dennison
UK
1 Thomas Road
Wooburn Green
Bucks HP10 0PE
Tel: 44 (0) 1628 859500
printers.uk@eu.averydennison.com