




MT-120019 MOUNTING KIT FOR FLAT PANEL ANTENNA



CONSTRUCTION

INSTALLATION METHOD	To Pole dia 2 3/4" – 3.5"
AZIMUTH RANGE: COARSE	±180°
AZIMUTH RANGE: FINE	None
TILT RANGE: COARSE	0° to -10°
TILT RANGE: FINE	None
AZIMUTH RESOLUTION STEP	None
TILT RESOLUTION STEP	None
WEIGHT	2.2 kg
PAY LOAD	20 kg (max)
MATERIALS	
BRACKETS	Steel, Zinc Plated per QQ-Z-325 type2 class1
CLAMPS	Steel, Zinc Plated per QQ-Z-325 type2 class1
FASTENERS	Steel, Zinc Plated per QQ-Z-325 type2 class1

[ADD TO COMPARISON](#) | [COMPARE](#)

ENVIRONMENTAL

TEMPERATURE	-55°C +71°C
VIBRATION	IEC 60721-3-4 4M5 Random
SHOCK MECHANICAL	IEC 60721-3-4 4M5
HUMIDITY	0-100%
ICE LOADING	25 mm Radial
SALT FOG	IEC 68-2-11 Ka, 500h
WIND LOAD (SURVIVAL)	103.6 kg
FRONT THRUST	8.6 kg
SIDE THRUST	
INSTALLATION INSTRUCTION DOCUMENT	RD41184700C

WAIVER!

While the information contained in this document has been carefully compiled to the best of our present knowledge, it is not intended as presentation or warranty of any kind on our part regarding the fitness of the products concerned for any particular use or purpose and neither shall any statement contained herein be construed as a recommendation to infringe any industrial property rights or as a license to use any such rights. The fitness of each product for any particular purpose must be checked beforehand with our specialists.

MTI Wireless Edge Ltd.

11 Hamelacha St. Afek Industrial Park Rosh Ha'ayin 48091, Israel
Tel: +972-3-9008900 | Fax: +972-3-9008901 | www.mtiwe.com