

Affordable Color Label Printing In a Compact Form

The perfect choice for small businesses.

The VP600 has been engineered for high performance while priced within reach of small to medium enterprises. Manufacturers struggling with the high cost of purchasing pre-printed labels and wastage associated with label design changes, damaged or obsolescence, will find the VP600 the must have printer.

With it's ease of use and superb image quality, the VP600 is the ideal choice for customers needing to print roll to roll, fanfold or tag stocks. The VP600 is the printer that will help get your products to retailers much quicker. It's time to "Get your labels printed your way, on your schedule and in the quantities you need".



Suitable for



Food & Beverage



Healthcare &
Nutraceuticals



Logistics




Manufacturing



Retail



Small/Medium
Enterprise



Specifications

GENERAL

Print Speed	6 and 8 ips (152.4 and 203.2 mm/s)
Print Resolution	1,600 x 1,600 dpi and 1,600 x 800 dpi
Print Width	2" - 8.5" (50.8 - 215.9 mm)
Communication	USB 2.0, 10/100Base-T
Inks	Dye Ink in 5 individual 200ml CYMCK color
Time to First Label	Less than 10 seconds
Dimensions (Printer)	20.1" (W) x 11.2" (H) x 15.2" (D) (510 x 285 x 385 mm)
Weight (Printer Only)	66 lbs (30 kg)

PRINTING

Print Modes	Roll-to-Cut, Roll-to-Roll, Print & Hold
Barcode PQ	1D Barcode ≥ Grade B (Code 39) with 10 mils bar width 2D Barcode ≥ Grade B (PDF417) with 10 mils cell size


OPERATION

Electrical	Universal power supply - 100 - 240 Vac, Peak current < 4A
Operating Temperature	15 to 35°C at RH 20 - 80%
Storage Temperature	-5 to 50°C
Standards/Approvals	FCC Part 15, Subpart B, Class A (US) IEC 60950-1 Compliance (International), cULus (US/Canada), CCC (China), RCM (Australia)
User Interface	Embedded web server Blacklit LCD control panel in 9 languages LED for Printer warnings and readiness indication Unobstructed accessibility to service bays for print head and ink tanks Designed for ease of setup, troubleshooting and service

MEDIA

Sensor Type	Gap, Reflective sensor for black mark
Media Types	Roll (Continuous, Die-cut), Fan-fold
Media Thickness	0.1 - 0.3 mm
Roll Diameter	6" (152 mm) OD with 3" Core (76.2 mm)
Supported Media	Glossy, Matte, Synthetic
Media Length	Up to 40" (1,016 m)
Construction	Metal casing with industrial grade ruggedness
What's in the Box	Printer (Integrated Un-winder), print head, ink cartridges, USB Cable and AC power cable
Built-in accessory	Automatic Cutter, Label Print and Hold
Warranty	1 Year limited warranty or 5 Million inches, whichever comes first

Overview




Angled Backlit LCD

Easy access to print engine & ink cartridge bays

External Un-winder for 6" OD roll

The VP600 supports all major MS Windows based label and graphics design applications like



Large 200ml ink cartridges

- 8.5" print width
- Up to 1,600 x 1,600 dpi
- Supports Roll-Roll, Roll-Cut, Print-Hold & Fan-Fold modes
- Automatic cutter
- Remote access via Embedded Web Server


- Ethernet 10/100Base-T
- USB 2.0
- Power Input

All connection ports are neatly designed and well placed at the back panel


Accessories

For more information, please visit us at www.vipcolor.com

Re-winder/Un-winder



Label Slitter



Matrix Remover & Slitter

