Cargo Trak II



The new Cargo Trak II was upgraded with a more rugged casing for outdoor and industrial use.

The new level of durability ensures (improves) tag lifetime of up to 10 years — even in harsh industrial environments — providing an even greater return on investment.



Superior read range

High performance yet cost-effective







Performance Characteristics

| Read range (On metal) ¹ | Up to 39 ft (12 m) |
|-------------------------------------|---|
| Read range (Off metal) ¹ | Up to 20 ft (6 m) |
| Polarization | Linear |
| Attachment | Rivet hole, ø 0.14 (3.5 mm), Adhesive (optional), Cable tie |

1. Fix reader

| i unctional opeenications | |
|-----------------------------|--|
| RF protocol | EPC global Class 1 Gen2 |
| Frequency | 902-928 (US) ; 865-868 (EU) |
| IC type (chip) ¹ | Alien Higgs-3 |
| Memory | 96-EPC bits, 64-bit unique TID, 512-bit user memory |
| Material | Anti-UV industry grade polymer |


Functional Specifications

1. The chip data retention is up to 50 years, based on chip operating under general environment conditions.

Radiation Pattern

- Freight Container Management
- Ourdoors Assets Tracking
- Heavy Equipment Inspections
- RTI Management

LEARN MORE >






Environmental Specifications


| Operational temperature | -40°C to +85°C |
|-------------------------|--------------------------------|
| Survival temperature | -40°C to +85°C |
| IP rating | IP68 |
| Compression strength | 29 psi (200 kPa) |
| Shock (drop) | 3 ft (1 m) to concrete/granite |
| Vibration | MIL-STD-810G |

| Product Dimensions and Weight | | |
|-------------------------------|-----------------------------------|--|
| Dimensions (in) | 3.94 x 1.02 x 0.35 | |
| Tolerance | +/- 0.02 | |
| Dimensions (mm) | 100 x 26 x 8.9 | |
| Tolerance | +/- 0.5 | |
| Rivet hole diameter | 0.137 in +/-0.008 (3.5 mm +/-0.2) | |
| Weight | 1.45 oz (41 g) | |





Installation Instructions



Instructions for optimal performances:

1.Drill two holes on the subject metal surface.

(ø 3.4 mm, picth: 88.7mm)

2.Insert two $\phi 3.2mm$ (recommended size) rivets on the tag. 3.Fix the tag on the metal surface with a rivet gun.

| Industry Compliance | | |
|---------------------|-------------------------|--|
| RoHS | EU Directive 2011/65/EU | |
| CE | Yes | |
| ATEX/IECEx | Compliant | |
| Warranty | 1 year | |

| Order Information | | |
|-------------------|---------------------|--|
| X03A2-US100-H3 | Cargo Trak II US | |
| X03A2-EU100-R6P | Cargo Trak II EU | |
| Optional service | Encoding / Printing | |

About Xerafy

Xerafy designs and manufactures the world's toughest RFID tags to power Industrial IoT applications in Aerospace, Oil & Gas, Automotive, Healthcare and Manufacturing. For Product inquiries: <u>sales@xerafy.com</u> Singapore | China | US | UK

GO TO WEBSITE>